

## Features & Benefits



**TELESCOPING TONGUE** - Puts the planter closer to the tractor in field position, allowing tighter turns on end rows.



**POSITIVE GROUND DRIVE FERTILIZER** - Large diameter spring-loaded steel wheel provides positive ground contact for excellent fertilizer metering accuracy.



**380/90 R46 TYRES** - Provide great flotation while being narrow enough to avoid running over any planter rows on single or twin-row spacing.



Bulk Liquid Fertilizer keeps you in the field longer between fillups

Folds to a narrow 4,15 m for safe and easy road transport; big 14,9 x 46 bar tyres roll easy with a large footprint, eliminating run-over rows on 76 cm or TR30"

25 series Openers feature 38 cm offset blades for better cutting performance, 25 cm of travel, Eliminator side-depth wheels, and patented clear-shot seed tubes

SPECIFICATIONS		
MODEL INFO 12 - 16 -row Yield-Pro Planters		
MODELS	YP-1625AHD	YP-1625AHL
ROW UNITS & ROW SPACING	TR76 cm / 32 rows TR91 cm / 32 rows TR91 cm / 24 rows 51 cm / 24 rows 76 cm / 16 rows 91 cm / 12 rows 91 cm / 16 rows	TR76 cm / 32 rows TR91 cm / 32 rows TR91 cm / 24 rows 38 cm / 31 rows 51 cm / 24 rows 76 cm / 16 rows 91 cm / 12 rows 91 cm / 16 rows
TYRE SIZE	Rear 380/90R46, Wing 15-19.5 NHS	
REQUIRED Kw	165 - 275	
DIMENSIONS		
WIDTH (NO MARKERS)	11,88 m / 14,63 m	
MARKERS WIDTH	11,98 m / 14,73 m	
TRANSPORT WIDTH	4,14 m	
TRANSPORT LENGTH	13,3 m / 14,1 m	
TRANSPORT CLEARANCE	510 mm	
TRANSPORT HEIGHT	3,84 m	
OPENER INFO		
OPENER SERIES	25 series	
OPENER DOWN PRESSURE	113 - 227 kg	
OPENER TRAVEL (UP-DOWN)	254 mm	
OPENER DEPTH RANGE	0 - 80 mm	
CAPACITIES		
SEED CAPACITY	56ℓ / Hopper	
FERTILIZER CAPACITY	3 500ℓ Dry 2 850ℓ Liquid	

### MORE ABOUT THE YP1625AHD & YP1625AHL:

Reduced refill times, various row-spacing options, and bulk-fill capacities enable Yield-Pro Planters to make you more money and save you more time than any comparable planter on the market.

The patented air manifold delivers seed on demand to the row unit meters without any moving parts, increasing reliability while decreasing maintenance costs and seed damage.

On the row unit, you have the choice of the Air-Pro® Seed Metering System with interchangeable seed plates for all crops, or a mechanical system with Precision Planting Population Max™ Finger Pickups or Singulator-Plus™ Meters to accurately singulate the seed for precise spacing.

A variety of row spacing options are available for our 12 row Yield-Pro Planters, which include 38, 51, 76, Twin-Row 76, and Twin- Row 91 cm spacings that are harvested with a standard 76 or 91 cm corn head.

Other options include: variable rate hydraulic drive, Keeton Seed Firmers®, Seed-Lok®, frame- or unit-mounted coulters, and/or row cleaners.

Contact us for more information:

086 111 3692 • info@agriafrika.co.za • www.agriafrika.co.za