

REDSTRIPE DRILL DRIVER ABR 20 PWR COMBI

This Impact Drill driver is a powerful and versatile tool designed for demanding professional applications. Its dual-speed gearbox provides the flexibility to switch between high-speed drilling and low-speed, high-torque fastening. The tool is compact and lightweight design reduces user fatigue and enhances maneuverability in tight or overhead spaces.



Voltage	20V
No-load speed	0-500/0-2000min
Torque adjusting positions	18+1+1
Maximum torque	95Nm
Chuck Size	13mm 1/2"
Impact rate	0~8500/0~34000 bpm
Max - drilling capability	Steel - 13mm Wood - 55mm Concrete - 16mm Brickwork - 16mm
Machine weight (bare tool)	1.25 kg

BRUSHLESS MOTOR

NEW

- High Power & Impact Performance: Designed for heavy-duty fastening and drilling tasks with reliable force and efficiency.
- Versatile Applications: Perfect for wood, metal, and masonry work.
- Compact & Balanced: Lightweight and ergonomic design reduces fatigue during extended use..
- LED with pre-light function for dark or poorly lit work area.
- All REDSTRIPE machines are compatible only with RED STRIPE batteries

ADVANTAGES

- G-Tec Active Anti-Twist technology ensures better torque control while the Anti-Kickback Protection minimizes sudden torque reactions for safer operation.

APPLICATIONS

Installing large screws or bolts into wood, metal, or masonry
 Framing, decking, and structural assembly
 Wood, metal, plastic, and light masonry drilling
 Holes for anchors, pipes, or fittings
 Electrical and plumbing installations
 Furniture or cabinet assembly
 Automotive and machinery repair
 Equipment or tool maintenance
 Compact design allows work in corners, overhead, or cramped areas

SAFETY INFORMATION

The operating temperature of tools and battery is -20°C to +60°C
 Allow cooling - If the tool or battery overheats and won't start, let both cool down before trying again.
 Drilling metal - Apply cutting oil to reduce wear and prevent excessive heat.
 Avoid overload - If the tool draws too much current, release the switch to stop, then restart once safe.

STORAGE CONDITION

The recommended storage temperature of tools and battery is from 0°C to 45°C
 Battery Storage: - Remove batteries from the tool when not in use.
 - Store partially charged batteries (around 40-60%) for long-term storage.
 - Avoid contact with metal objects to prevent short circuits.

USAGE RESTRICTIONS

Do not expose power tools to rain or wet conditions. Water entering a power tool will increase the risk of electric shock.
 Do not operate power tools in explosive atmospheres, such as in the presence of flammable liquids, gases or dust.
 Avoid over-tightening screws to prevent stripping.

CROSS SELLING

Drill Bits
 Bit Holder & Extensions
 Cutting oil/ Drilling lubricants
 PPE products

Description	Battery type	Qty of battery	Charger type	Qty of charge	Packaging	Art. no.	P. Qty.
20V DRILL DRIVER SET	4Ah	1	20v - 4A	1	Injected plastic case	5702 514 011	1

*Packaging - INJECTED PLASTIC CASE

PACKAGING

