

## Multigrade compressor oil Pro

High-value synthetic oil with additive specifically tailored for use in air-conditioning compressor technology

Compatible with following refrigerants: R-23, R-125, R-134a, R-1234yf, R-227, R-413a, R-407c, R-410a, R-404a, R-507

Can be mixed with PAG oil and ester oil

Excellent lubricating effect

- Longer compressor service life
- High level of refrigerant compression in the compressor



Contents	1000 ml
----------	---------

Art. no. 0892 764 123

P. Qty.: 1 / 6

### Details/Application

For universal maintenance and lubrication of vehicle air-conditioning compressors in the refrigerant circuit. Suitable for refrigerants R-134a, R-1234yf and other HFC and HFO refrigerants. Suitable for all cars, trucks, buses and agricultural machines equipped with R-134a or R-1234yf air-conditioning systems.

### Instructions

Top up low compressor oil according to the amount recommended by the vehicle manufacturer and add to the air-conditioning circuit via the air-conditioning service unit.

The usage instructions are recommendations based on the tests we have conducted and our experience; carry out your own tests before each application. Due to the large number of applications and storage and processing conditions, we do not assume any liability for a specific application result. Insofar as our free customer service provides technical information or acts as an advisory service, no responsibility is assumed by this service except where the advice or information given falls within the scope of our specified, contractually agreed service or the advisor was acting deliberately. We guarantee the consistent quality of our products. We reserve the right to make technical changes and further develop products.

Related products for	Designation	Art. no.
0892 764 123	Filling adapter	0764 000 124