



AGRI UTTO 10W-30

Description

TORQ AGRI UTTO 10W-30 is a premium grade Universal Tractor Transmission Oil (UTTO) for use in power take-offs, transmissions, hydraulic systems, wet brakes and other auxiliary systems found in modern tractors and other off-highway equipment. TORQ AGRI UTTO 10W-30 is formulated to meet all leading tractor manufacturer's specification.

Application

- Suited for mechanical transmissions, gearboxes, reduction drives, bevel gears, wet brakes and hydraulic systems.
- Can also be used in power take offs and wet clutches and hydrostatic steering systems.

Benefits

- Will minimize the number of lubricants required on a variety of agricultural machinery.
- Excellent seal compatibility.
- Anti-foaming additives to prevent sump overflow.
- Superior wear control ensuring long engine life.
- Excellent cleaning and anti-wear protection ensure loading capacity in extreme working conditions.
- The oils friction characteristics will eliminate screeching in wet brakes and the sliding action in power take-offs.
- Excellent anti-oxidation and shear stability characteristics are a result of the latest additive technology.

Performance Level

- API GL-4
- AGCO POWERFLUID 821XL
- FORD ESN-M2C 134
- CASE NEW HOLLAND CNH MAT3505/3509/3525
- FNHA-2-C200.00
- JOHN DEERE JDN J20C/J20D
- MASSEY FERGUSON CMS M1135/1141/1143/1145
- WHITE FARM (AGCO) Q-186



PRODUCT CHARACTERISTICS

PROPERTIES	UNITS	VALUE	TEST METHOD
SAE GRADE		10W-30	
DENSITY @ 20°C	kg/L	0.887	ASTM D4052
VISCOSITY @ 40°C	cSt	67.0	ASTM D445
VISCOSITY @ 100°C	cSt	9.8	ASTM D445
VISCOSITY INDEX	n/a	152	ASTM D2270
POUR POINT	°C	-32	ASTM D97
FLASH POINT	°C	230	ASTM D92
SULPHATED ASH	%M/M	0.9	ASTM D874
TBN	mgKOH/gm	9.5	ASTM D2896

The information and figures given here are typical of current production and conform to specification, minor variations may occur.