

## **BRAVA+**

Higher harvesting efficiency



**BRAVA +**

# HIGHLY EFFICIENT HARVEST

Brava + corn head harvests different types of corn efficiently, with quality, and profitability.

## **Deck plates**

They feature electric adjustment\*. It's activated through a remote control. The adjustment is performed easily and quickly and according to the maize plant stalk. As a result, the harvest is higher efficient even with different variates.

*\* The adjustment of the deck plates is either mechanical or electrical*

## **Coupling system**

It is compatible with any harvester model. It requires the hitch structure changing only.

## **Side fairing**

Lighter and more resistant, it avoids the loss of cobs at the corn head ends.

## **Torque limiter on the auger**


It provides greater safety during the harvest operation, avoiding damages to the system in case of locking or overloading.

## **Torque limiter for each row unit**

The torque limiters are individual with disarming radial system that ensures a longer assembly lifespan and avoids the disarming of row units that are not being blocked.

## **Side transmission gearbox**

It is grease-bathed, and has an efficient self-compensator tensioner with a spring, enabling the reverse activation without damaging the system.



## **Side auger assembly\***



It harvests the snapped corn plants on the corn head sides where they are conducted to the head interior side, avoiding crop losses.

*\* Optional feature*



## **Height sensor\***

It allows for operations close to the ground. Available for models above 13 row units. It is provided with kits of 3, 4, or 5 sensors.

*\* Optional feature ( Contact the Sales Department)*



**ADJUSTABLE  
ROW  
UNIT  
ASSEMBLY**

- STALK ROLLS WITH 8 VANES
- GATHERING CHAINS WITH 6 LUGS
- MORE THAN 10 ROTATION OPTIONS IN THE GEARBOX



**30%**

**LESS STRAW FED THROUGH THE HARVESTER  
LESS FUEL CONSUMPTION  
HIGHER OPERATIONAL YIELD**

## TECHNICAL SPECIFICATIONS

### BRAVA +

Chassis	Row units	Spacing	Kg	Total width	Chassis	Row units	Spacing	Kg	Total width
3180	7	45 cm	1,625 kg	3,400 mm	7240	16	45 cm	3,600 kg	7,460 mm
3180	4	90 cm	990 kg	3,400 mm	7350	10	75 cm	2,475 kg	7,570 mm
3630	8	45 cm	1,750 kg	3,850 mm	7350	14	52,5 cm	3,029 kg	7,570 mm
3630	7	50 cm	1,605 kg	3,850 mm	7490	15	50 cm	3,522 kg	7,710 mm
3630	6	60 cm	1,460kg	3,850 mm	7690	17	45 cm	3,800 kg	7,910 mm
4080	9	45 cm	1,975 kg	4,300 mm	7690	14	55 cm	3,605 kg	7,910 mm
4080	8	50 cm	1,830 kg	4,300 mm	7690	9	90 cm	3,030 kg	7,910 mm
4080	6	70 cm	1,525 kg	4,300 mm	7980	16	50 cm	3,482 kg	8,200 mm
4080	5	90 cm	1,405 kg	4,300 mm	8140	18	45 cm	4,000 kg	8,360 mm
4330	6	75 cm	1,850 kg	4,550 mm	8280	12	70 cm	3,240 kg	8,500 mm
4530	10	45 cm	2,182 kg	4,750 mm	8280	14	60 cm	3,430 kg	8,500 mm
4530	9	50 cm	2,035 kg	4,750 mm	8280	16	52 cm	3,742 kg	8,500 mm
4980	11	45 cm	2,370 kg	5,200 mm	8580	19	45 cm	4,215 kg	8,800 mm
4980	10	50 cm	2,225 kg	5,200 mm	8580	17	50 cm	4,095 kg	8,800 mm
4980	6	90 cm	1,690 kg	5,200 mm	8730	16	55 cm	3,570 kg	8,950 mm
5430	12	45 cm	2,579 kg	5,650 mm	8730	10	90 cm	2,695 kg	8,950 mm
5430	8	70 cm	2,162 kg	5,650 mm	9030	20	45 cm	4,354 kg	9,250 mm
5430	7	80 cm	2,070 kg	5,650 mm	9030	18	50 cm	4,104 kg	9,250 mm
5880	13	45 cm	2,795 kg	6,100 mm	9480	21	45 cm	4,474 kg	9,700 mm
5880	10	60 cm	2,386 kg	6,100 mm	9480	19	50 cm	4,234 kg	9,700 mm
5880	8	75 cm	2,077 kg	6,100 mm	9480	16	60 cm	4,115 kg	9,700 mm
5880	7	90 cm	1,942 kg	6,100 mm	9980	22	45 cm	4,644 kg	10,200 mm
5990	12	50 cm	2,795 kg	6,210 mm	9980	20	50 cm	4,524 kg	10,200 mm
6360	14	45 cm	2,990 kg	6,580 mm	9980	18	55 cm	4,420 kg	10,200 mm
6530	13	50 cm	2,889 kg	6,750 mm	10390	23	90 cm	3,250 kg	10,610 mm
6850	15	45 cm	3,190 kg	7,070 mm	10390	12	45 cm	4,850 kg	10,610 mm
6850	10	70 cm	2,760 kg	7,070 mm	10850	24	45 cm	5,400 kg	11,070 mm
6850	8	90 cm	2,176 kg	7,070 mm	11780	26	45 cm	5,850 kg	12,000 mm
7080	14	50 cm	3,070 kg	7,300 mm	11990	24	50 cm	5,430 kg	12,210 mm
7080	12	60 cm	2,830 kg	7,300 mm					

The Marketing Department reserves the right to make changes on the product features without previous notice. Images are only illustrative.

Print: 16 December 2024  
Update: 16 December 2024

*Note: the implement dimensions, weight and capacity, are approximate and are subject to changes without any previous modifications.*

## LEARN MORE

Position your mobile phone on the QR code to read it and check it out!

### Video

See for yourself, Brava + operation quality in the crop field.



### Website

Access Brava + on Stara website for more information.



THIS SPACE IS INTENDED FOR DEALERSHIP DATA

[www.stara.com.br/en](http://www.stara.com.br/en)

STARA S.A. Agricultural Implements Industry | Av. Stara, 519 - Post office box 53 - Não-Me-Toque/RS - Brazil - Phone/Fax: (0xx54) 3332 2800 | Postcode: 99470-000 | Email address: faleconosco@stara.com.br

[LinkedIn/Company/Stara](#) - [YouTube/StaraBrasil](#) - [f/StaraBrasil](#) - [@StaraBrasil](#)