

Features & Benefits



HYDRAULICALLY ADJUSTABLE GANG ANGLE
- Turbo-Max allows you to change the gang angle from 0 to 6 degrees on the go to match it to field conditions.



HYDRAULIC WEIGHT TRANSFER - Transfer valve adjusts weight from center to wings, providing even, constant down pressure to the full width.



19 CM BLADE SPACING - Two gangs, each with 19 cm spacing between coulters, with the rear gang offset from the front gang. The gangs work together to size residue to an industry leading 9,53 cm.



MORE ABOUT THE TURBO-MAX:

The Turbo-Max® takes true vertical machining to new heights. The ability to form an unmatched seed bed through more aggressive leveling of the soil, improved cutting of plant residues and unsurpassed residue coverage while continuing to work in the vertical plane makes Turbo-Max truly unique in the industry. Turbo-Max offers the perfect cultivation of fields that are uneven due to sprayer, harvester or tractor tracks, and reduces wind erosion through better residue coverage. With its coulters spacing of 19 cm and coulters group angles hydraulically adjustable from 0 to 6 degrees, Turbo-Max offers all the benefits of true vertical machining with just one tool.

SPECIFICATIONS

MODEL INFO TURBO-MAX: SHALLOW VERTICAL TILLAGE

MODELS	1200TM	1500TM	1800TM	2400TM	3000TM	3500TM	4000TM
COULTER SPACING	95 mm (2offset gangs at 254 spacing per gang)						
TYRES	11Lx15F-ply (4)	12,5 x15F-ply (4)	380/55R 16,5 (2)	380/55 R17	380/55R 16,5 (4)	40/55 R18 (4)	440/55 R18 (4)
WEIGHT*	5,398 kg	6,033kg	8,895 kg	10,664 kg	13,569 kg	15,183 kg	17,366 kg
kW	8 - 10 kW per ft / 24 - 30 kW per meter						
DIMENSIONS (m)							
TILLAGE WIDTH	4,01 m	4,78 m	5,49 m	7,44 m	9,35 m	10,67 m	12,19 m
TRANSPORT WIDTH	4,27 m	4,91 m	4,27 m	4,69 m	4,69 m	5,15 m	5,49 m
TRANSPORT HEIGHT	1,65 m	1,65 m	2,53 m	3,44 m	4,27 m	4,39 m	4,33 m

Contact us for more information:

086 111 3692 • info@agriafrika.co.za • www.agriafrika.co.za