

COOLIUS® A10 vehicle air-conditioning service unit

Easy-to-use, mobile companion for air-conditioning servicing on R134a units

Efficient in mobile use

- Innovative scales construction with transport lock
- Highest level of impact reduction
- Can be operated with a voltage converter

Sophisticated documentation

- Data exported to Excel via USB interface
- Documentation of individual services
- Evaluation of total refrigerant consumption

Quick change of oil type, e.g. PAG to POE oil

Intelligent rinsing of the pipe system and service hoses

Long service intervals

Use of high-quality and specially designed components

No unwanted access

Personalised access using a 4-digit password

Scope of delivery

- 2 x 3 m service hoses with standard quick-action couplings
- Vehicle fill level database
- Stickers for various oils and UV additives
- Maintenance book
- Abridged operating instructions (with website link for multi-lingual operating instructions)
- Device instructions



Weight of device	65 kg
Width	572 mm
Height	1045 mm
Depth	545 mm
Type of refrigerant	R134a
Refrigerant volume	11 kg
Refrigerant filling accuracy	+/- 15 g
Vacuum pump output	100 l/min
Suction capacity	300 g/min
Display	4-line LCD
Max. operating pressure	20 bar
Approval	CE
Product weight (per item)	65.2 kg

Art. no. W050 101 000

P. Qty.: 1

Details/Application

Air-conditioning servicing on air-conditioning units in cars, vans, utility vehicles, construction vehicles and agricultural vehicles.

Related products for	Designation	Art. no.
W050 101 000	Removal adapter set R134a For 12 kg R134a reusable refrigerant bottles	0764 000 003
	Air-conditioning refrigerant R134 a	0892 764 001
	POE oil POE 100	0892 764 045
	Multigrade compressor oil Pro 1000 ml	0892 764 123
	Basic UV leak detection additive	0892 764 134
	AIRCO-BAG air-conditioning leak detection additive	0892 764 071
	PAG oil Premium AIRCO-BAG	0892 764 072
	PAG oil Premium AIRCO-BAG	0892 764 073
	POE oil AIRCO-BAG	0892 764 074