

## Multi-purpose grease IV

### Synthetic high-performance grease with white solid lubricants

- Suitable for food-contact areas
- EP additives for high pressure resistance
- Excellent dry-running properties
- Good sealing effect and corrosion protection



Soap base	Al complex
Lubricant code	KPFHC2R-40
Min./max. temperature conditions	-45 to 180 °C
Colour	White
NLGI grade/conditions	2/with DIN 51818
Base oil viscosity, kinematic/conditions	350 mm <sup>2</sup> /s/at 40 °C
Min. dripping point/conditions	250 °C/in accordance with DIN ISO 2176
Min./max. worked penetration/conditions	285 x 0.1 mm-285 x 0.1 mm/in accordance with DIN ISO 2137
Corrosion protection period/category	Corrosion category 0
VKA welding load	3000 N
Shelf life from production	24 Month
Oil basis	Synthetic

Weight of content	Container	Art. no.	P. Qty.
0.4 kg	Cartridge	<b>0893 107 003</b>	1/24
25 kg	Pail	<b>0893 107 253</b>	1

### Details/Application

Synthetic high-performance grease with white solid lubricants for the food industry.



### Instructions

Clean the lubricating point thoroughly before filling for the first time. Apply a thin and even coat to the parts to be lubricated. Observe the bearing manufacturer's specifications! Avoid mixing with other greases wherever possible. If used in areas in which food is processed or stored, only the minimum quantity technically necessary may be used.

## Proof of performance

NSF H1-registered (no.: 135924), meets the requirements of USDA 1998 H1. The product may come into contact with foodstuffs for technical reasons.



## Notice

Greases are delivered in plastic cartridges! The plastic cartridges improve storage (they prevent the grease from oozing out at high temperature). Store cartridges upright in a cool, dry place! The operating instructions of the vehicle, machinery and assembly manufacturers must be observed.

The usage instructions are recommendations based on the tests we have conducted and on our experience; carry out your own tests before each application. Due to the large number of applications and storage and processing conditions, we do not assume any liability for a specific application result. Insofar as our free customer service provides technical information or acts as an advisory service, no responsibility is assumed by this service except where the advice or information given falls within the scope of our specified, contractually agreed service or the advisor was acting deliberately. We guarantee the consistent quality of our products. We reserve the right to make technical changes and further develop products.

Related products	Art. no.
Hand-lever grease gun For 400 g cartridges	<b>0986 00</b>
Double-handed grease gun Suitable for 500 g screwed cartridge	<b>0986 000 002</b>
Single-handed grease gun With variable pressure setting directly on handle Suitable for 400 g - pull off cartridge	<b>0986 000 010</b>
Single-handed grease gun With variable pressure setting directly on handle Suitable for 400 g - lube shuttle cartridge	<b>0986 000 011</b>
Single-handed grease gun With variable pressure setting directly on handle Suitable for 500 g screwed cartridge	<b>0986 000 012</b>
Metal feed piece For hand-lever grease gun	<b>0986 001</b>
Reinforced rubber hose For one-handed, two-handed grease gun and lever grease gun	<b>0986 002</b>
Chuck For hand-lever grease guns	<b>0986 003</b>
Easylock grease coupling	<b>0986 004 001</b>
Combination filling appliance	<b>0986 02</b>
Lube-Shuttle® hand-lever grease gun	<b>0986 05</b>