




## Safety and comfort features

- Acoustic and visual alarm if the temperature is too low or too high, as well as when the machine runs out of gas.
- Heat sensor that stops the gas supply if the burner goes out.
- The sound insulation in the machine prevents condensation and is fireproof.
- If the outlet is not mounted, the engine will not start (R20 and R25).
- If the machine is still in the blocked transport position, the engine will not start.
- Possibility to equip with an Auto Start System. This can also be mounted later as an option.
- Possibility to equip with a wireless transmitter, connected to a remote station. This can be used to start or stop the Revolution with a remote temperature sensor and to follow all data on a computer.

	<b>Revolution 20</b>	<b>Revolution 25</b>	<b>Revolution 30</b>
			
Outlet	Fix, 20 cm from the ground	Fix, 100 cm from the ground	Rotating, above the machine
Application	Orchards, some vineyards, greenhouses	Lower crops like strawberries	Vineyards, greenhouses, high crops like raspberries
Protected Area	Between 0,7 and 1 ha	Approx. 1 ha	Approx. 1 ha
Air Distribution	Machine rotates 360°	Machine rotates 360°	Outlet rotates 360°
Dimensions (LxWxH) in mm	1200 x 775 x 1200	1200 x 775 x 1200	1200 x 775 x 1550
Weight	325 kg	325 kg	325 kg
Gas Consumption	10,5 kg/h	10,5 kg/h	10,5 kg/h