

TECHNICAL DATA SHEET

Rust converter spray

Art. no. 0893 110 400

P. Qty.: 1 / 12

Corrosion protection paint with rust-conversion properties

- Stops the corrosion process
- Provides lasting protection for all metallic surfaces
- Creates a high-quality epoxy primer to enable further processing
- Offers reliable protection in the form of an acid-free formulation
- Protects within cracks and pores too due to excellent penetration properties

Contents	400 ml
Colour	Colourless
Shelf life from production	24 Month
Max. temperature resistance	100 °C



Application area

Rust converter spray neutralises the rusted layer and forms a metal-organic iron aggregate. The corrosion protection paint with rust-converting properties is ideal for repainting heavily rusted areas. For maintenance and long-lasting protection of vehicles, systems, machinery and components in all applications.

Application information

- Remove loose rust, grease, dirt and coats of paint under which rust has formed. Clean the rust spot thoroughly.
- Before use, shake the can vigorously, then spray on 3-4 thin layers (spray distance approx. 25-30 cm).
- Can be recoated after approx. 2 hours. For enhanced corrosion protection, repainting with a top coat is recommended.

Notice

Cures at room temperature. After use, turn the can upside down and spray until the valve is empty. Only 1-component products should be used when painting over.

This information is only a recommendation based on our experience. Preliminary testing is required. The information in the technical data sheet must be read prior to application. When painting over, we recommend that you only use 1-component products. The specifications of the coating manufacturer must be observed. Only for industrial users/specialists.

TECHNICAL DATA SHEET

The usage instructions are recommendations based on the tests we have conducted and our experience; carry out your own tests before each application. Due to the large number of applications and storage and processing conditions, we do not assume any liability for a specific application result. Insofar as our free customer service provides technical information or acts as an advisory service, no responsibility is assumed by this service except where the advice or information given falls within the scope of our specified, contractually agreed service or the advisor was acting deliberately. We guarantee consistent quality of our products. We reserve the right to make technical changes and further develop products.